



minipack® - torre
Packaging machines and systems

TUNNEL 70 DIGIT

Dual-chamber heat-shrinking tunnel - Tunnel mouth 680x390 mm



DESCRIPTION

TUNNEL 70 DIGIT is the largest version of the **shrink tunnel** line. The machine is equipped with a host of updated technical and aesthetic features that are designed to meet a number of packaging needs. The shrink wrap tunnel is flexible and versatile, and can operate with a wide variety of heat-shrink films.

TECHNICAL FEATURES

minipack®-torre S.p.A.

Sede legale - Via Provinciale, 54 - 24044 DALMINE (BG) Italy

P.IVA - C.F.: 01633550163 - Capitale sociale 619.200,00 i.v. - Reg. Imprese di Bergamo 01633550163 - REA n. 224151



Electrical power supply	200V 50/60Hz 3Ph 208V 60Hz 3Ph 220V 50/60Hz 3Ph 400V 50/60Hz 3Ph
MAX power installed	14 kW (200V) 15 kW (208V) 14 kW(220V) 14,5 kW (400V)
Maximum current	38 A (200V) 43 A (208V) 34 A (220V) 21 A (400V)
MAX product size	680x390 mm xL. (The maximum length depends on the shape, conveyor belt speed and type of film, etc.)
Machine Dimensions	2770x1160x1640 mm
Machine weight (Net/Gross)	415/483 kg
Tunnel infeed dimensions	680x390 mm

minipack®-torre shall not be held liable for typos or printing errors in this catalogue. It also reserves the right to make changes to the specified features without prior notice. All trademarks are property of their respective owners and are hereby acknowledged.

TECHNICAL DRAWING

[Layout Tunnel 70](#)



• **Technical features**

- Manual belt height adjustment
- Digital display with 9 programs that can be selected and customised
- Option of selecting the auto-rotating feature for the rollers
- Product conveyor
- Adjustable double air baffles
- Auto-off program
- Outfeed roller conveyor provided as standard
- Two separate chambers with temperature control.